



The Next Phase
In Loudspeaker
Technology



T Series

| Specifications | T1220U | T1222U | T1540 | T1522 | T1840 |
|-------------------------|--------------------------|------------------------------|----------------------------------|--------------------------------------|------------------------------|
| Frequency Response | 70Hz - 16 kHz | 70Hz - 16 kHz | 50Hz - 16kHz | 50Hz - 16kHz | 45Hz - 500Hz |
| Continuous Program | 400 Watts | 400 Watts | 800 Watts | 800 Watts | 800 Watts |
| Nominal Impedance | 8 ohms | 8 ohms | 8 ohms | 8 ohms | 4 ohms |
| Sensitivity (1w/1m) | 99dB | 99dB | 99dB | 99dB | 99dB |
| Max Peak SPL | 128 dB @ 1 meter | 128 dB @ 1 meter | 131 dB @ 1 meter | 131 dB @ 1 meter | 131 dB @ 1 meter |
| Nominal Coverage Angles | 120" H x 60" V | 120" H x 60" V | 90" H x 40" V | 120" H x 60" V | na |
| Crossover Frequency | 3 kHz | 3 kHz | 2 kHz | 3 kHz | 100 Hz |
| Dimensions | 24" H x 15" W x 16" D | 21" H x 15" W x 14 3/8" D | 27 5/8" H x 18" W x 18 7/8" D | 23 3/4" H x 17 1/2" W x 18 7/8" D | 25 1/2" H x 22" W x 19" D |
| Ship Weight | 62 lbs. | 57 lbs | 76 lbs. | 67 lbs. | 81 lbs. |

Professional Audio Systems

2270 Cosmos Court, Carlsbad, CA 92009, USA

Voice: (760) 431-9924 Fax: (760) 431-9496 Web: www.pas-toc.com

E-Mail: info@pas-toc.com